



VA-SUDHA CHEMICALS PVT. LTD.

(An ISO 9001 Company & cGMP Certified • Crisil Rated 2A • Reach Pre-Registered • Kosher Certified)

Manufacturers of : SPECIALITY CHEMICALS & DRUGS INTERMEDIATES

CIN : U24110MH1986PTC039676

Office : 5th Floor, Sai Ashish-A, Balrajeshwar Road, Mulund (W), Mumbai - 400 080, India.

Tel.: +91-22-2164 4382 / 2164 0407 / 2164 3827 • Fax : +91-22-2164 3680

E-mail : vasudha@vasudhachem.com • Website : www.vasudhachem.com



VASUDHAPOL PE 0015

VASUDHAPOL PE 0015 is PEG 1500 having average molecular weight of 1500g/mol.

PROPERTIES: VASUDHAPOL PE 0015 White or almost white solid with a waxy or paraffin- like appearance.

SPECIFICATIONS:	pH (5% aqueous solution)	: 4.5- 7.5
	Hydroxyl Value	: 70- 80
	Freezing point	: 42- 48°C
	Moisture %	: Max. 1.0%
	Sulfated Ash	: Max. 0.2%

SOLUBILITY: VASUDHAPOL PE 0015 is Very soluble in water and in methylene chloride, freely soluble in alcohol, practically insoluble in fatty oils and in mineral oils.

STABILITY: The Shelf Life /Re-evaluation period for this product is 36 months from date of manufacture.

APPLICATION VASUDHAPOL PE 0015 Carrier for epoxy adhesives, Reactant with isocyanate in urethane adhesives, Ceramic glaze, Chemical intermediates, Inks, Lubricants, Modifier for water-dispersible alkyd resins in paints and coating applications, old release agent, Plasticizer, Penetrant and protectant in wood stains, Solvent and flow control in aqueous dispersion thermoset coatings, Base and carrier in tarnish remover, Lubrication and consistency in abrasives

TOXICITY: VASUDHAPOL PE 0015 has extremely low systemic toxicity. There are no adverse dermatological effects.